



Loft ladders
and wall hatches





A classic symbol of Swedish quality

Design and functionality that will last for generations. These are the fundamental concepts in our product development. From idea to reality, we carefully follow certain guidelines to ensure, both for our own peace of mind and for the end user's, that every detail is of the highest quality. One of these guidelines is to use durable materials and deliver strong designs, aspects we see as being the classic symbol of Swedish quality. We have thirty year's experience in the development of loft ladders and wall hatches for contemporary homes and public environments. Our goal is to create the preconditions for individual choices and unique alternatives and to meet demanding aesthetics, practical utility and safety issue requirements. We have been one of the world's leading brands within this area for many years and have sold our products all around the world. Please, take a closer look at our range on the following pages.



For demanding environments

MidMade's range of loft ladders and wall hatches include something for every application. From classic 3-section wooden ladders with fire standard compliant hatches to wall hatches in white elegant, moulded compound for exclusive home environments.

Our range features twelve loft ladders, four wall hatches and a series of supplementary products and accessories which provide the main products with a number of additional benefits. These include extremely low U-values for home environments with high energy requirements, increased safety and the opportunity to find the right design for confined spaces or spaces which are higher than normal.

The main materials used in our products are slow growth spruce, aluminium and elegant, moulded compound. The wall hatches can be both right and left hung and are insulated to meet Nordic and European standards for fire protection, draught and energy efficiency requirements. We use heavy layers of polystyrene and rockwool, which also automatically adapts our simpler products to demanding environments.

MidMade stands for the freedom to find the right solution which will perform well for many years. All production is carried out at our quality controlled factory in Timrå, Sweden, under the watchful eyes of experienced designers. This is a reassuring guarantee for those who value high standards.



Product					Accessories				
	Outer frame measurements (mm)	Insulation	U-value*	Fire standard in wood	Extension section in alu	Extension section D1003	Guard rail universal	Hand rail for passive houses	Upper hatch
LEX 30	540x1130 / 670x1130	30mm polystyrene	0.82	no	x		x	x	
LEX 70	540x1130 / 700x1130	70mm polystyrene	0.40	no	x		x	x	x
LEX 60	540x1130 / 700x1130	60mm rockwool	1.00	EI 30	x		x	x	x
LEX 70 SAX	540x820 / 540x1130 / 700x1130	70mm polystyrene	0.40	no			x		
LEX 60 SAX	540x820 / 540x1130 / 700x1130	60mm rockwool	1.00	no			x		
ISO 30	580x1180 / 680x1180	30mm polystyrene	0.82	no	x		x	x	
ISO 70	580x1180 / 680x1180 680x1280 / 680x1380	70mm polystyrene	0.40	no	x		x	x	
LUX A1120	570x1116	50mm polystyrene	0.54	no	x		x	x	x
LUX A1220	570x1116	50mm polystyrene	0.54	no		x	x	x	x
LUX PROFFS A5220	606x1136	50mm rockwool	0.61	EI 60		x	x		
LUX PROFFS A5230	736x1436	50mm rockwool	0.61	EI 60		x			
LUX PROFFS SAX	606x836 / 606x1136	50mm rockwool	0.61	EI 60			x		
SAN 70	540x790 / 580x1100	70mm polystyrene	0.41	no					
SAN 60	540x790 / 580x1100	60mm rockwool	1.00	EI 30					
LUX B1010 / B1020	570x800 / 570x1100	50mm polystyrene	0.54	no					
LUX PROFFS B5010/B5020	570x800 / 570x1100	50mm rockwool	0.61	EI 60					
LEX D70 upper hatch	570x1100 / 540x1130	70mm polystyrene	0.20**	no					
LUX D1020 upper hatch	700x1130 / 680x1280 570x1100	50mm polystyrene	0.33***	no					

* U-value determination carried out by SP Technical Research Institute of Sweden.
 ** Calculated in combination with loft ladder LEX 70 and ISO 70
 *** Calculated in combination with loft ladder LUX A1120.



LEX This loft ladder is available with a slow grown spruce standard ladder or aluminium scissors ladder. Heavily insulated hatch, standard model or fire standard EI30 compliant. Models in the series: LEX 30/70/60 and LEX SAX 70/60.



ISO 3-section loft ladder in slow grown spruce with lighter or heavier insulation and coverable hatch. Models in the series: ISO 30 and ISO 70.



LUX Loft ladder with slow grown spruce or aluminium 3-section ladder. Hatch with high quality white moulded compound finish. Models in the series: LUX A1120 and LUX A1220.



LUX PROFFS Loft ladder with aluminium 3-section or scissors ladder. Sheet steel hatch, compliant with fire standard EI60. Models in the series: LUX PROFFS A5220/5230 and LUX PROFFS SAX.



SAN Flexible and highly insulated wall hatch, standard model also available as fire standard EI30. Models in the series: SAN 70 and SAN 60. Can be custom manufactured.



LUX Insulated white moulded compound wall hatch with integrated liner and high quality finish. Models in the series: LUX B1010 and LUX B1020.



LUX PROFFS Strong sheet steel wall hatch with insulation and integrated fire standard EI60 compliant liner. Models in the series: LUX B5010 and LUX B5020.



UPPER HATCH Supplementary product for extremely low U-value. Available in two models, adapted to LEX, ISO and LUX loft ladders. Models in the series: LEX D70 and LUX D1020.

